

# SC-1200

N-2-(Aminoethyl)-3-aminopropyltrimethoxysilane

#### PRODUCT DESCRIPTION


SC-1200 is a colorless liquid with a special ammonia smell, soluble in alcohols, chain hydrocarbons, aromatic hydrocarbons and other solvents.

### **TYPICAL PRODUCT DATA\*** \* Value when leaving plant **Property** Unit Typical Value CAS# 1760-24-3 Colorless transparent Appearance liquid 261°C **Boiling** point °C Flash Point °C 128°C (closed cup) Refractive index °C 1.4425 (25°C) Density 1.03 $(25^{\circ}\text{C}, \text{g/ml})$ % ≥97% Purity

### PACKAGING AND AVAILABILITY

SC-1200 is available in 200 kgs drums.

## **TECHNICAL DATA SHEET**



### TYPICAL FEATURES AND APPLICATIONS

SC-1200 is a bifunctional organosilane possessing reactive primary amine and hydrolysable inorganic methoxysilyl groups. The dual nature of its reaction, it can organically bond inorganic materials and organic polymers.

SC-1200 is an important additive in many fields: as glass fiber treatment agent, or wetting agent additives; primer for glass and metal; primer or adhesion promoter for sealants and adhesives; as an additive or primer to improve substrate adhesion for paints and coatings.

### INFORMATION FOR USE

In the presence of water, the methoxy groups of SC-1200 hydrolyze to form reactive silanol groups which can bond to a variety of inorganic substrates. SC-1200 has the organic properties of diamino group(s) that can react with suitable organic polymers.

### SHELF LIFE AND STORAGE

In the unopened original container, shelf life is 12 months.

Store in a cool, well ventilated place. Keep container tightly closed.

PRODUCT SAFETY INFORMATION REQUIRED FOR SAFE USE IS NOT INCLUDED IN THIS DOCUMENT. BEFORE HANDLING, READ SAFETY DATA SHEET AND CONTAINER LABELS FOR SAFE USE, PHYSICAL, ENVIRONMENTAL, AND HEALTH HAZARD INFORMATION.

LIMITATIONS: Not intended for human injection. This product is neither tested nor represented as suitable for medical or pharmaceutical uses.

Limited Warranty: Silsource Inc. warrants to Buyer that for a period of 12 months from the date of manufacture of the products, such products will materially conform to Silsource Inc.'s specifications in effect as of the date of manufacture. This warranty does not apply where the products have (a) been subjected to abuse, misuse, neglect, negligence, accident, improper testing, improper installation, improper storage, improper handling, abnormal physical stress, abnormal environmental conditions, or use contrary to any instructions issued by Silsource Inc.; (b) been reconstructed, repaired, or altered by persons other than Silsource Inc. or its authorized representatives; or (c) been used with any third-party product or hardware that has not been previously approved in writing by Silsource Inc. Buyer's exclusive remedy for breach of the limited warranty shall be a refund of the purchase price or replacement of the product, at Silsource Inc.'s sole discretion.

Disclaimer: EXCEPT FOR THE EXPRESS LIMITED WARRANTY SET OUT ABOVE, SILSOURCE INC. MAKES NO WARRANTY WHATSOEVER WITH RESPECT TO THE GOODS, INCLUDING ANY (A) WARRANTY OR CONDITION OF MERCHANTABILITY; (B) WARRANTY OR CONDITION OF FITNESS FOR A PARTICULAR PURPOSE; (C) WARRANTY OR CONDITION OF TITLE; OR (D) WARRANTY AGAINST INFRINGEMENT OF INTELLECTUAL PROPERTY RIGHTS OF A THIRD PARTY, WHETHER EXPRESS OR IMPLIED AND WHETHER ARISING BY LAW, COURSE OF DEALING, COURSE OF PERFORMANCE, USAGE OF TRADE, OR OTHERWISE. BUYER ACKNOWLEDGES THAT IT HAS NOT RELIED UPON ANY REPRESENTATION, CONDITION, OR WARRANTY MADE BY SILSOURCE INC., OR ANY OTHER PERSON ON SILSOURCE INC.'S BEHALF, EXCEPT AS SPECIFICALLY PROVIDED ABOVE.

VERSION: 2.0 Last updated: 23/SEP/2024

<sup>\*</sup> These values are not intended to be used as specifications but as suggested characteristics