

TECHNICAL DATA SHEET

SC-3200

γ-Glycidoxypropyltriethoxysilane

PRODUCT DESCRIPTION

TYPICAL FEATURES AND APPLICATIONS

SC-3200 is a clear, colorless, low-odor liquid.

SC-3200 may be used as an adhesion promoter (coupling agent) for organic/inorganic interfaces, as a surface modifier (e.g. regulating surface polarity) or as a crosslinking agent (moisture-curing of polymers).

TYPICAL PRODUCT DATA

(not intended for use in preparing specifications)

<u>CAS#</u> 2602-34-8 <u>Formula:</u> C₁₂H₂₆O₅Si

<u>Appearance:</u> Colorless transparent liquid

Refractive

Index: @25°C 1.425

Min Purity: 98%

Density: 1.004

(25°C)

Boiling: 124°C [3mmHg]

Flash Point: 110°C

SC-3200 may improve dry/wet strength in cured composites reinforced with glass fiber rovings. SC-3200 may enhance wet electrical properties of epoxy-based encapsulate and packaging materials and may eliminate the need for a separate primer in polysulfide and urethane sealants. SC-3200 may improve adhesion in waterborne acrylic sealants, urethane/epoxy coatings.

INFORMATION FOR USE

SC-3200 is miscible with practically all organic solvents and enters into the typical reactions of an organic epoxide with acids, alcohols etc.

AVAILABLE PACKAGING

SC-3200 is available in 200 kgs drums or 1000 kgs IBC container

SHELF LIFE AND STORAGE

In the unopened original container, shelf life is 12 months. Store in a cool, temperature controlled, well ventilated place. Keep container tightly closed.

PRODUCT SAFETY INFORMATION REQUIRED FOR SAFE USE IS NOT INCLUDED IN THIS DOCUMENT. BEFORE HANDLING, READ PRODUCT AND SAFETY DATA SHEET AND CONTAINER LABELS FOR SAFE USE, PHYSICAL, ENVIRONMENTAL, AND HEALTH HAZARD INFORMATION.

LIMITATIONS Not intended for human injection. This product is neither tested nor represented as suitable for medical or pharmaceutical uses.

Limited Warranty: Silsource Inc. warrants to Buyer that for a period of 12 months from the date of manufacture of the products, such products will materially conform to Silsource Inc.'s specifications in effect as of the date of manufacture. This warranty does not apply where the products have (a) been subjected to abuse, misuse, neglect, negligence, accident, improper testing, improper installation, improper storage, improper handling, abnormal physical stress, abnormal environmental conditions, or use contrary to any instructions issued by Silsource Inc.; (b) been reconstructed, repaired, or altered by persons other than Silsource Inc. or its authorized representatives; or (c) been used with any third-party product or hardware that has not been previously approved in writing by Silsource Inc. Buyer's exclusive remedy for breach of the limited warranty shall be a refund of the purchase price or replacement of the product, at Silsource Inc.'s sole discretion.

Disclaimer: EXCEPT FOR THE EXPRESS LIMITED WARRANTY SET OUT ABOVE, SILSOURCE INC. MAKES NO WARRANTY WHATSOEVER WITH RESPECT TO THE GOODS, INCLUDING ANY (A) WARRANTY OR CONDITION OF MERCHANTABILITY; (B) WARRANTY OR CONDITION OF FITNESS FOR A PARTICULAR PURPOSE; (C) WARRANTY OR CONDITION OF TITLE; OR (D) WARRANTY AGAINST INFRINGEMENT OF INTELLECTUAL PROPERTY RIGHTS OF A THIRD PARTY, WHETHER EXPRESS OR IMPLIED AND WHETHER ARISING BY LAW, COURSE OF DEALING, COURSE OF PERFORMANCE, USAGE OF TRADE, OR OTHERWISE. BUYER ACKNOWLEDGES THAT IT HAS NOT RELIED UPON ANY REPRESENTATION, CONDITION, OR WARRANTY MADE BY SILSOURCE INC., OR ANY OTHER PERSON ON SILSOURCE INC.'S BEHALF, EXCEPT AS SPECIFICALLY PROVIDED

DATE: 10/03/2022 VERSION: 1.1