

## SF6000P

MethylHydrogen silicone fluid

### PRODUCT DESCRIPTION

SF6000P is a methyl hydrogen silicone fluid with some of the radical methyl groups of the dimethyl silicone are replaced by hydrogen.

#### TYPICAL PRODUCT DATA\*

\* Value when leaving plant

Property	Unit	Typical Value
CAS#	-	63148-57-2 or 9004-73-3
Appearance	-	Transparent liquid
Viscosity (25°C)	°C	20-25cst
Hydrogen Content	-	1.5~1.7%
Volatile Content (105°C, 3 Hrs)	%	<2%
Flash Point (Closed cup)	°C	>115°C

\* These values are not intended to be used as specifications but as

### PACKAGING AND AVAILABILITY

SF6000P is available in 980 Kg IBC tote containers.


Samples are available upon request.

PRODUCT SAFETY INFORMATION REQUIRED FOR SAFE USE IS NOT INCLUDED IN THIS DOCUMENT. BEFORE HANDLING, READ SAFETY DATA SHEET AND CONTAINER LABELS FOR SAFE USE, PHYSICAL, ENVIRONMENTAL, AND HEALTH HAZARD INFORMATION.

**LIMITATIONS:** Not intended for human injection. This product is neither tested nor represented as suitable for medical or pharmaceutical uses.

**Limited Warranty:** Silsource Inc. warrants to Buyer that for a period of 24 months from the date of manufacture of the products, such products will materially conform to Silsource Inc.'s specifications in effect as of the date of manufacture. This warranty does not apply where the products have (a) been subjected to abuse, misuse, neglect, negligence, accident, improper testing, improper installation, improper storage, improper handling, abnormal physical stress, abnormal environmental conditions, or use contrary to any instructions issued by Silsource Inc.; (b) been reconstructed, repaired, or altered by persons other than Silsource Inc. or its authorized representatives; or (c) been used with any third-party product or hardware that has not been previously approved in writing by Silsource Inc. Buyer's exclusive remedy for breach of the limited warranty shall be a refund of the purchase price or replacement of the product, at Silsource Inc.'s sole discretion.

**Disclaimer:** EXCEPT FOR THE EXPRESS LIMITED WARRANTY SET OUT ABOVE, SILSOURCE INC. MAKES NO WARRANTY WHATSOEVER WITH RESPECT TO THE GOODS, INCLUDING ANY (A) WARRANTY OR CONDITION OF MERCHANTABILITY; (B) WARRANTY OR CONDITION OF FITNESS FOR A PARTICULAR PURPOSE; (C) WARRANTY OR CONDITION OF TITLE; OR (D) WARRANTY AGAINST INFRINGEMENT OF INTELLECTUAL PROPERTY RIGHTS OF A THIRD PARTY, WHETHER EXPRESS OR IMPLIED AND WHETHER ARISING BY LAW, COURSE OF DEALING, COURSE OF PERFORMANCE, USAGE OF TRADE, OR OTHERWISE. BUYER ACKNOWLEDGES THAT IT HAS NOT RELIED UPON ANY REPRESENTATION, CONDITION, OR WARRANTY MADE BY SILSOURCE INC., OR ANY OTHER PERSON ON SILSOURCE INC.'S BEHALF, EXCEPT AS SPECIFICALLY PROVIDED ABOVE.



### TYPICAL FEATURES AND APPLICATIONS

SF6000P can be used as a fabric treatment, in the chemical synthesis of modified silicone fluids and to impart water repellency and moisture proofing.

SF6000P can be used to treat powders for water repellency. It is a reactive product with good releasability.

### INFORMATION FOR USE

Applications are varied with usage levels that vary from 1-80% depending on the application.

SF6000P can be used as a cross linker for silicone addition type rubbers, as well as a hydrophobic agent, lubricant and anti-sticking agent. Used as an intermediate in the synthesis of modified silicone oils such as polyether and alkyl based fluids. The Si-H bonds that are readily available can be used to react with chemicals containing double bonds or hydroxyl groups.

Ensure adequate ventilation. Open and handle container with care. Avoid heat, open flames, and other sources of ignition.

### SHELF LIFE AND STORAGE

Store in a cool, dry environment with ventilation and away from heat, flames and incompatible materials. This product has a minimum shelf life of 24 months.